

INSTALLATION INSTRUCTIONS

IN THE BOX:

- TS2516 Belisha Beacon Shroud
- 8 x Pop Rivets

TOOLS REQUIRED:

- Electric Drill
- 4.5mm Metal Drill Bit
- Pop Rivet Gun

The TS2516 Belisha Beacon Shroud is supplied with 8 pre-drilled holes and 8 black topped pop rivets.

INSTALLATION:

<p>1. Place the TS2516 Shroud over the Amber globe of the Belisha Beacon in the desired position.</p>	<p>2. Mark the Amber globe through the pre-drilled holes of the TS2516 Shroud.</p>
<p>3. Once the position of the holes are marked – use the 4.5mm drill bit to drill holes into the Amber Globe – these should match up with the TS2516 Shroud holes.</p>	<p>4. Re-position the TS2516 Shroud and insert the pop rivets into the holes – ensuring the rivet goes through both the TS2516 Shroud and Amber globe hole.</p>
<p>5. Use the pop rivet gun to secure each rivet and ensure the TS2516 Shroud is securely fixed.</p>	

For further assistance – please do not hesitate to contact us.

Email: info@pwssigns.com

www.pwssigns.com

PWS Signs Ltd.,
Ravensdale,
Unit 10 Northlink Business Park,
Coes Road,
Dundalk,
Co. Louth,
A91 WV09
Tel: 042-9375010

PWS Ireland Ltd.,
Ballincraig Way,
Greenbank Industrial Estate,
Newry,
Co. Down,
BT34 2QX
Tel: 028-30264511

